

Quad Screen Splitter LCD Console Drawer – FHD

DVI-D, USB, Audio, Hub



↑ (USB Port for device access)



Switching port by simply moving the mouse cursor across each screen boundary on QSS mode

Quad Screen Splitter (QSS) LCD console drawers represents the latest technology in KVM switching. The key advantage over conventional KVM switches is that it allows you to simultaneously display and administer 4 computers on a single console. It combines KVM features and a digital multi-viewer scaling and converting videos at both inputs and output.

Configure with 17.3 inch A-Grade FHD LCD panels, integrated 4 ports DVI-D/USB/Audio/HUB, support Full screen and Quad screen mode.

The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Features

- 1U single rail with 17.3" LCD Monitor,
- Support FHD with 1080p resolution.
- Four Independent DVI-D/USB/Audio/HUB interface for each PC.
- Support Full screen and Quad screen mode
- On Quad Screen mode, by Mouse moving across screen boundary or via Push Button or Hotkey to switching port
- Front 1 x , rear 2x USB 2.0 Type A, Sharing USB peripheral Device for each computer. (Ex, flash disk, hard driver, KB/Mouse)
- Build in 2x2w stereo speakers.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra convenience.

Rear of KVM-1704WQSS-M2



Part No.		KVM-1704WQSS-M2
Direct no. of Computers		4 x DVI-D/ USB / Audio & 2x HUB
Maximum no. of Computers		4
LCD	Size	17.3"
	Backlight	LED
	Resolution	1920*1080 FULL HD (support up to 1920*1200)
	Max.color	262K
	Luminance	300cd/m2
	View Angel (H/V)	140 / 120
Contrast Ratio		650 : 1
Port Selection		Mouse moving across screen boundary , Push Button or Hotkey
USB HUB		Front 1 x , rear 2x USB 2.0 Type A for USB Peripheral Device
KB/Mouse Emulation		USB
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)
Power		100-240V AC 50/60Hz via IEC Type power cord
Environment		Operation temp: 0 to 50℃
		Storage temp: -20 to 60℃
		Humidity: 10% - 90%, non-condensing
		Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP
Physical Dimensions / Net Weights		448x42x580mm (WxHxD) / 12.5KG
Packing Dimensions / Gross weights		720x190x800mm (WxHxD) / 18.5KG
Accessory		
1.8meter IEC Type Power Cord ,1.8meter DVI Cable x4 , 1.8meter USB Cable x 4 , 1.8meter Audio Cable x 4		

Specifications subject to change without notice

Quad Screen Splitter LCD Console Drawer – FHD

DVI-D, USB, Audio, Hub



Rear of KVM-1704WQSS-M2

