


Combo CAT6 KVM Switch


Optimize rack space. Maximize rack monitoring



Rear of KCC-108E



Rear of KCC-116E



Rear of KCC-132E

Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



Features

- Capable of connecting 32, 16 or 8 servers in 1U.
- Support combo interface VGA-USB & VGA-PS/2.
- Up to 40 meters between server to KVM switch.
- USB local console, optional remote IP console.
- Cascade up to 8 levels, support mixed CAT6 & DB15 Combo KVM switch.
- Mixed PS2/USB/SUN & MAC with multi-platform switch Capability.
- Auto scan for monitoring PCs, easy select via push button, Hot keys and OSD.
- Hot pluggable, no software or driver required.
- Easy and quick installation.

Part No.		KCC-108E	KCC-116E	KCC-132E
No. of Computers		8	16	32
Max. no. of Computers		232 (Daisy Chain)	240 (Daisy Chain)	256 (Daisy Chain)
KVM port connector		RJ 45		
Local Console		1x HD DB15 for VGA (up to 1920x1440 resolution) 2x USB Type A for KB / Mouse		
Optional IP Remote Console		1x RJ45 connector for 10/100M Ethernet (up to 1600x1200 resolution) 1x DB9 male connector for modem, Null modem and serial power control 1x mini USB 2.0 receptacle		
Daisy Chain		1x DB15 (Female), up to 8 levels		
Hot keys		Scroll-Lock, Caps-Lock, Num-Lock, Alt-Ctrl-Win		
Compatibility		Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix		
Power		100-240V AC 50/60Hz external power adapter		
Environment		Operation temp.: 0 to 50°C Storage temp.: -20 to 60°C Humidity : 10% - 90%, non-condensing		
Physical Dimensions / Net Weights		448mm (W) x 167mm (D) x 44mm (H) / 3kg		
Packing Dimensions / Gross Weights		560*120*250mm / 3.5kg		
Relate Items				
DGU	CAT6 KVM Dongle - USB & VGA		DGP	CAT6 KVM Dongle - PS/2 & VGA
DGD	CAT6 KVM Dongle-USB&DVI		DIP-101	KVM over IP Module for Remote Bios Level Access

Specifications subject to change without notice