

IPM-SS1261

12-inch IP66 Waterproof Stainless Steel Monitor

Features

- 12.1" TFT LCD Monitor with Resolution up to 1024 x 768
- IP66/NEMA4X Waterproof, Stainless Steel Housing
- 500nits High Brightness / 1000nits Sunlight Readable (Optional)
- Resistive Touch Screen (Optional)
- Wide Temperature -30°~+60°C (Optional)



SPECIFICATION

Display	Size/Panel Type	12.1 TFT LCD Panel
	Resolution	1024 x 768
	Brightness (cd/m ²)	500cd/m ² / (Optional: 1000 cd/m ²)
	Contrast Ratio	700:1
	Response Time	35 ms
	Backlight	LED Backlight Unit
	Colors	16.2M Colors
	Viewing Angle (H/V)	160°/160°
	Surface Hardness	7~8H, AR Glass
Touch Screen	Touch Screen Type	Resistive Touch (Optional)
	Surface Hardness	3H
Environment	Operating Temperature	0°~+50°C
	Storage Temperature	-20°C~+60°C
	Humidity	5%~95% RH(Non-Condensing)
	Waterproof Rating	IP66/NEMA4X, 6 Side Waterproof
System	OSD	Menu, Auto, On/Off, Up, Down
	I/O Interface	DVI x 1, VGA x 1, Power in x 1
	Power Input	12V DC (Optional: 9~36V DC)
	Power Consumption	22W
	Certification	FCC/CE/RoHS Compliance
	Mounting	VESA 75 x 75mm; 100 x 100mm, M4/depth:4.5mm
	Dimension/Weight	347mm (W) x 292mm (H) x 64mm (D)/6.3kgs

ORDERING CODE

IPM-SS1261 | T | -HB | -W




T = Touch Screen (Resistive)

-HB = High Brightness (1000nits)

-W = Wide Temperature, -30°~+60°C

ACCESSORIES

- DVI Cable x 1 (1.8M)
- VGA Cable x 1 (1.8M)
- Power Cable x 1 (1.8M)



Unit: mm