

PPC-SS2200

21.5" True Flat Stainless Steel Panel PC, IP66 waterproof,
VESA mount, Projected Capacitive Touch



Features

- 21.5" True Flat Stainless Steel Panel PC
- IP66, NEMA 4X equivalent waterproof enclosure
- 350 cd/m² brightness, LED backlight unit (Optional 1000 cd/m²)
- 2 point Projected Capacitive Touch
- Built in Intel QM77 chipset with Intel® i5-2510E 2.5GHz Processor
- VESA 100x100mm, 100 x 200mm mount
- VGA, DVI, HDMI COM x 1, LAN x 2, USB x 4, Audio
- DC 24V input, 62W power consumption

Specifications

Display	Size/Panel Type	21.5" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m ²)	350 cd/m ² (Optional 1000 cd/m ²)
	Contrast Ratio	50000:1
	Response Time	16 ms
	Backlight	LED backlight unit
	Color	16.7M Colors
	Viewing Angle(H/V)	178° /168°
Front Bezel	Touch Sensor	2 Point Projective Capacitive Touch
	Surface Hardness	7~8 H
System	CPU	Intel i5-2510E 2.5 GHz Processor, 1 MB cache 1.86 GHz
	Chipset	QM77
	BIOS	AMI
	Memory	4 GB DDR3 1600/1333 SO-DIMM SDRAM
	Storage	2.5" 32/64/128 GB SSD
	Back Panel I/O	DVI, VGA, HDMI, LAN x 2, USB x 4, Audio Jack x 1, COM x 1
Power	Power Input	DC 24 V, AC/DC Power Adapter x 1
	Power Consumption	62W
Mechanical	Mounting	VESA 100 x 100mm, 200 x 100mm
	Dimension / Weight	537.8mm (W) x 329.3mm (H) x 80.5mm (D) /13 kgs
	Housing Material / Color	Stainless Steel / Silver
Environment	Operating Temperature	0° C ~ +50° C
	Storage Temperature	-20° C ~ +60° C
	Humidity	10%~95% RH (Non-Condensing)
	Waterproof Rating	IP66/NEMA4X Waterproof
	Certification	FCC/CE/RoHS Compliance

Ordering:

- ❖ PPC-SS2260-QM-HB-W
- ❖ -HB = High Brightness (1000 nits)
- ❖ -W = Wide Temperature (-30° C ~ +60° C)

