

PPC-SS2460

24" Stainless Steel Panel PC, IP66 waterproof, VESA mount, Projected Capacitive Touch



Features

- 24" True Flat Stainless Steel Panel PC
- IP66, NEMA 4X equivalent waterproof enclosure
- 350 cd/m² brightness, LED backlight unit (Optional 1000 cd/m²)
- 2 point Projected Capacitive Touch
- Built in Intel N2930 2.16GHz Processor
- VESA 100x100mm, 200 x 200mm mount
- COM x 1, LAN x 2, USB x 1
- AC 100 ~ 240 V input, 70W power consumption

Specifications

Display	Size/Panel Type	24" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m ²)	300 cd/m ²
	Contrast Ratio	50000:1
	Response Time	25 ms
	Backlight	LED backlight unit
	Color	16.7M Colors
	Viewing Angle(H/V)	178° /168°
Front Bezel	Touch Sensor	2 Point Projective Capacitive Touch
	Surface Hardness	7 H
System	CPU	Intel N2930 2.16 GHz Processor
	BIOS	UEFI
	Memory	Max. 8 GB Dual Channel DDR3 1333 SO-DIMM SDRAM
	Storage	2.5" 32/64/128 GB SSD
	Back Panel I/O	LAN x 1, USB x 4, COM x 1
	Expansion Slot	1 x Mini PCIe
Power	Power Input	AC 100~240 V input with Power Adapter x 1
	Power Consumption	70W
Mechanical	Mounting	VESA 100 x 100mm, 200 x 200mm
	Dimension / Weight	537.8mm (W) x 329.3mm (H) x 80.5mm (D) /13 kgs
	Housing Material / Color	Stainless Steel / Silver
Environment	Operating Temperature	0° C ~ +50° C
	Storage Temperature	-20° C ~ +60° C
	Humidity	10%~95% RH (Non-Condensing)
	Waterproof Rating	IP66/NEMA4X Waterproof
	Certification	FCC/CE/RoHS Compliance

