

PPC-SS3260

31.5" Stainless Steel Panel PC, IP66 waterproof, VESA mount, Projected Capacitive Touch



Features

- 31.5" Stainless Steel Panel PC with 1920 x 1080 Resolution
- IP66, NEMA 4X equivalent waterproof enclosure
- 350 cd/m² brightness, LED backlight unit (Optional 1000 cd/m²)
- 2 point Projected Capacitive Touch
- Built in Intel Atom D2553 Dual Core 1.86GHz Processor
- VESA 100x100mm, 200 x 200mm mount
- COM x 1, LAN x 2, USB x 2
- AC 100 ~ 240 V input, 85W power consumption
- Wide temperature -30° C ~ +60° C and IR touch (optional)

Specifications

Display	Size/Panel Type	31.5" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m ²)	350 cd/m ²
	Contrast Ratio	3000:1
	Response Time	8 ms
	Backlight	LED backlight unit
	Color	16.7M Colors
Viewing Angle(H/V)		178° /168°
Front Bezel	Touch Sensor	2 Point Projective Capacitive Touch
	Surface Hardness	7 H, AR Glass
System	CPU	Intel Atom D2550 1.86 GHz Processor
	BIOS	NM10
	Memory	4 GB Dual Channel DDR3 1066 SO-DIMM SDRAM
	Storage	2.5" 32/64/128 GB SSD
	Back Panel I/O	LAN x 1, USB x 4, COM x 1
	Expansion Slot	1 x Mini PCIE
Power	Power Input	AC 100~240 V input with Power Adapter x 1
	Power Consumption	70W
Mechanical	Mounting	400 x 300 mm, M6/depth:6mm
	Dimension / Weight	815mm (W) x 506mm (H) x 87mm (D) /40 kgs
	Housing Material / Color	Stainless Steel / Silver
Environment	Operating Temperature	0° C ~ +50° C
	Storage Temperature	-20° C ~ +60° C
	Humidity	10%~95% RH (Non-Condensing)
	Waterproof Rating	IP66/NEMA4X Waterproof
	Certification	FCC/CE/RoHS Compliance

Ordering:

- ❖ PPC-SS3260-T-HB-W
- ❖ T = Touch Screen (IR Touch)
- ❖ -HB = High Brightness (1000 nits)
- ❖ -W = Wide Temperature (-30° C ~ +60° C)

